


PNP General Purpose Amplifier



SOT-323

Features

- Epoxy meets UL-94 V-0 flammability rating and halogen free
- Moisture Sensitivity Level 1
- Part no. with suffix "Q" means AEC-Q101 qualified

Applications

- PNP General purpose switching and amplification

Mechanical Data

- Case: SOT-323
- Terminals: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- Marking:

BC856AWQ	3A
BC856BWQ	3B
BC857AWQ	3E
BC857BWQ	3F
BC857CWQ	3G
BC858AWQ	3J
BC858BWQ	3K
BC858CWQ	3L

■ Maximum Ratings (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Value	
			BC856	BC857
Collector-Base Voltage	V_{CBO}	V	BC856	-80
			BC857	-50
			BC858	-30
Collector-Emitter Voltage	V_{CEO}	V	BC856	-65
			BC857	-45
			BC858	-30
Emitter-Base Voltage	V_{EBO}	V	-5	
Collector Current -Continuous	I_C	mA	-100	
Total Device Dissipation	P_D	mW	200	
Junction Temperature	T_j	°C	-55 to +150	
Storage Temperature	T_{STG}	°C	-55 to +150	



BC856AWQ THRU BC858CWQ

RoHS
COMPLIANT

■ Electrical Characteristics (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base breakdown voltage	V_{CBO}	V	BC856	$I_C = -10\mu A, I_E = 0$	-80	
			BC857		-50	
			BC858		-30	
Collector-emitter breakdown voltage	V_{CEO}	V	BC856	$I_C = -10mA, I_B = 0$	-65	
			BC857		-45	
			BC858		-30	
Emitter-base breakdown voltage	V_{EBO}	V	$I_E = -1\mu A, I_C = 0$	-5		
Collector-base cut-off current	I_{CBO}	μA	$V_{CB} = -30V, I_E = 0$			-0.1
Emitter-base cut-off current	I_{EBO}	μA	$V_{EB} = -5V, I_C = 0$			-0.1
DC current gain	h_{FE}		BC856AWQ, BC857AWQ, BC858AWQ	$V_{CE} = -5V, I_C = -2mA$	125	250
			BC856BWQ, BC857BWQ, BC858BWQ		220	475
			BC857CWQ, BC858CWQ		420	800
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	$I_C = -100mA, I_B = -5mA$			-0.65
Base-emitter saturation voltage	$V_{BE(sat)}$	V	$I_C = -100mA, I_B = -5mA$			-1.1

■ Other Characteristics (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Transition frequency	f_T	MHz	$V_{CE} = -5V, I_C = -10mA, f = 100MHz$	100		

■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
BC856AWQ THRU BC858CWQ	F2	Approximate 0.005	3000	30000	120000	7" reel









BC856AWQ THRU BC858CWQ

RoHS
COMPLIANT

■ Characteristics(Typical)

BC857BWQ






BC856AWQ THRU BC858CWQ


RoHS
COMPLIANT

■ SOT-323 Package Outline Dimensions



SYMBOL	DIMENSIONS			
	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.043	0.900	1.100
A1	0.000	0.004	0.000	0.100
A2	0.035	0.039	0.900	1.000
b	0.006	0.016	0.150	0.400
c	0.004	0.010	0.100	0.250
D	0.071	0.087	1.800	2.200
E	0.045	0.053	1.150	1.350
E1	0.085	0.096	2.150	2.450
e	0.026TYP		0.650TYP	
e1	0.047	0.055	1.200	1.400
L	0.021REF		0.525REF	
L1	0.010	0.018	0.260	0.460
θ	0°	8°	0°	8°

■ SOT-323 Suggested Pad Layout



Unit: mm



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, life-sustaining, or military. Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.