

Schottky Barrier Rectifier



Features


- V_R 70V
- I_F 70mA

Typical Applications

- Low Forward Voltage Drop

Mechanical Data

- **Package:** SOD-323
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end
- **Marking:** K73



■Maximum Ratings (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	VALUE
Repetitive peak reverse voltage	V_{RRM}	V	70
Reverse voltage	V_R	V	70
Average forward current	I_F	mA	70
Non-repetitive Peak Forward Surge Current @ 8.3ms Half Sine	I_{FSM}	mA	100
Power Dissipation	P_D	mW	200
Thermal Resistance Junction to Ambient Air	$R_{\theta JA}$	°C/W	500
Maximum junction temperature	T_J	°C	125
Storage temperature range	T_{stg}	°C	-55 to +150

■Electrical Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Conditions	Min	Max
Forward voltage	V_{F1}	V	$I_F=1mA$,	-	0.41
	V_{F2}	V	$I_F=15mA$,	-	1
Reverse current	I_R	nA	$V_R=50V$	-	100
Breakdown voltage	$V_{(BR)}$	V	$I_R=10uA$	70	-
Diode capacitance	C_J	pF	$V_R=1V, f=1MHz$	-	2
Reverse Recovery Time	T_{RR}	ns	$I_F=I_R=10mA, R_L=100\Omega, I_{rr}=1mA$	-	5







BAS70WS

Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
BAS70WS	F2	Approximate 0.0048	3000	30000	120000	7" reel


Characteristics (Typical)






BAS70WS

■Outline Dimensions



DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MIN	MAX
A	---	0.0393	---	1.0000
A1	0.0000	0.0039	0.0000	0.1000
A2	0.0314	0.0354	0.8000	0.9000
b	0.0098	0.0157	0.2500	0.4000
c	0.0031	0.0059	0.0800	0.1500
D	0.0472	0.0551	1.2000	1.4000
E	0.0629	0.0709	1.6000	1.8000
E1	0.0984	0.1063	2.5000	2.7000
L	0.0187TYP		0.475TYP	
L1	0.0098	0.0157	0.250	0.400
e	0°	8°	0°	8°

■Soldering Footprint



UNIT : mm

SUGGESTED SOLDER PAD LAYOUT



BAS70WS

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com> , or consult your nearest Yangjie's sales office for further assistance.